


 LoadSafe

KU 8100

8x100A 690V AC-22

| | |
|----------------|-------------------|
| PRODUCT NUMBER | 20355 |
| GTIN | 6419410203552 |
| E-NUMBER FI | 3600797 |
| TECHNICAL NAME | 8x100A 690V AC-22 |
| ETIM CLASS | EC000216 |


MEASUREMENTS

| | |
|------------|-----------|
| HEIGHT | 103 mm |
| WIDTH | 100 mm |
| DEPTH | 188 mm |
| VOLUME | 1.9364 l |
| NET WEIGHT | 1.6359 kg |

LOGISTICAL DATA

| | |
|----------------|-----------|
| SALES UNIT | 1 |
| PACKAGE SIZE 1 | 1 |
| PACKAGE SIZE 1 | 188 mm |
| DEPTH | |
| PACKAGE SIZE 1 | 103 mm |
| HEIGHT | |
| PACKAGE SIZE 1 | 188 mm |
| WIDTH | |
| PACKAGE SIZE 1 | 1.6359 kg |
| WEIGHT | |
| PACKAGE SIZE 1 | 3.6404 l |
| VOLUME | |

DIMENSIONAL DRAWING



TECHNICAL DATA

| | |
|--|-----|
| NUMBER OF POLES | 8 |
| ATEX | No |
| RATED OPERATIONAL CURRENT AC-23A 415 V, IE (A) | 100 |
| RATED OPERATIONAL CURRENT AC-23A 690 V, IE (A) | 63 |
| RATED OPERATIONAL POWER, 3- PHASE 1500 RPM SQUIRREL-CAGE MOTOR AC-23A 690 V (KW) | 55 |
| RATED INSULATION VOLTAGE, UI (V) | 800 |
| NOMINAL VALUES WITH CABLE SIZE (MM ²) | 70 |
| RATED THERMAL CURRENT, ITH (A) | 125 |
| RATED OPERATIONAL CURRENT AC-21A 415 V, IE (A) | 125 |
| RATED OPERATIONAL CURRENT AC-21A 500 V, IE (A) | 125 |
| RATED OPERATIONAL CURRENT AC-21A 690 V, IE (A) | 125 |
| RATED OPERATIONAL CURRENT AC-22A 415 V, IE (A) | 100 |
| RATED OPERATIONAL CURRENT AC-22A 500 V, IE (A) | 100 |
| RATED OPERATIONAL CURRENT AC-22A 690 V, IE (A) | 100 |
| RATED OPERATIONAL CURRENT AC-23A 500 V, IE (A) | 63 |
| RATED OPERATIONAL POWER, 3- PHASE 1500 RPM SQUIRREL-CAGE MOTOR AC-23A 415 V (KW) | 55 |

| | |
|---|-------------------|
| RATED OPERATIONAL POWER, 3-PHASE 1500 RPM SQUIRREL-CAGE MOTOR AC-23A 500 V (KW) | 37 |
| RATED FUSED SHORT-CIRCUIT CURRENT, BACK-UP FUSE OPTION 1 (A) | 160 |
| RATED FUSED SHORT-CIRCUIT CURRENT, R.M.S. IQ OPTION 1 (KA) | 65 |
| RATED FUSED SHORT-CIRCUIT CURRENT, PEAK VALUE (KA) | 15 |
| RATED IMPULSE WITHSTAND VOLTAGE, UIMP (KV) | 8 |
| RATED SHORT-CIRCUIT MAKING CAPACITY, ICM 690 V (KA) | 8 |
| RATED SHORT-TIME WITHSTAND CURRENT 1 S, ICW 690 V (KA) | 5 |
| RATED BREAKING CAPACITY, AC-23A 415 V (A) | 800 |
| RATED BREAKING CAPACITY, AC-23A 500 V (A) | 504 |
| RATED BREAKING CAPACITY, AC-23A 690 V (A) | 504 |
| ELECTRICAL ENDURANCE (NUMBER OF OPERATIONS) | 2000 |
| MECHANICAL ENDURANCE (NUMBER OF OPERATIONS) | 16000 |
| TERMINAL / BOLT SIZE CU (MM ²) | 6..70 |
| MAXIMUM TERMINAL TORQUE (NM) | 6 |
| SWITCH TYPE | Load Break Switch |