

 **LoadSafe****KU 3630****LVK228LKX150YR****3x630A 690V AC-22**

| | |
|----------------|-------------------|
| PRODUCT NUMBER | 29272 |
| GTIN | 6419410292723 |
| TECHNICAL NAME | 3x630A 690V AC-22 |
| ETIM CLASS | EC000216 |

MEASUREMENTS

| | |
|------------|-----------|
| HEIGHT | 258.4 mm |
| WIDTH | 279.4 mm |
| DEPTH | 125 mm |
| VOLUME | 9.0246 l |
| NET WEIGHT | 5.7313 kg |

DIMENSIONAL DRAWING

LOGISTICAL DATA

| | |
|--------------------------|-----------|
| SALES UNIT | 1 |
| PACKAGE SIZE 1 | 1 |
| PACKAGE SIZE 1 WEIGHT | 5.7313 kg |

TECHNICAL DATA

| | |
|--|-------|
| NUMBER OF POLES | 3 |
| RATED OPERATIONAL CURRENT AC-23A 415 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-23A 690 V, IE (A) | 630 |
| RATED OPERATIONAL POWER, 3- PHASE 1500 RPM SQUIRREL-CAGE MOTOR AC-23A 690 V (KW) | 630 |
| RATED INSULATION VOLTAGE, UI (V) | 1000 |
| NOMINAL VALUES WITH CABLE SIZE (MM ²) | 2*185 |
| RATED THERMAL CURRENT, ITH (A) | 630 |
| RATED OPERATIONAL CURRENT AC-21A 415 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-21A 500 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-21A 690 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-22A 415 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-22A 500 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-22A 690 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-23A 240 V, IE (A) | 630 |
| RATED OPERATIONAL CURRENT AC-23A 500 V, IE (A) | 630 |
| RATED OPERATIONAL POWER, 3- PHASE 1500 RPM SQUIRREL-CAGE MOTOR AC-23A 415 V (KW) | 355 |

| | |
|---|-------------------|
| RATED OPERATIONAL POWER, 3-PHASE 1500 RPM SQUIRREL-CAGE MOTOR AC-23A 500 V (KW) | 400 |
| RATED FUSED SHORT-CIRCUIT CURRENT, BACK-UP FUSE OPTION 1 (A) | 800 |
| RATED FUSED SHORT-CIRCUIT CURRENT, R.M.S. IQ OPTION 1 (KA) | 100 |
| RATED FUSED SHORT-CIRCUIT CURRENT, PEAK VALUE (KA) | 76 |
| RATED IMPULSE WITHSTAND VOLTAGE, UIMP (KV) | 12 |
| RATED SHORT-CIRCUIT MAKING CAPACITY, ICM 690 V (KA) | 60 |
| RATED SHORT-TIME WITHSTAND CURRENT 1 S, ICW 1000 V (KA) | 28 |
| RATED BREAKING CAPACITY, AC-23A 415 V (A) | 5040 |
| RATED BREAKING CAPACITY, AC-23A 500 V (A) | 5040 |
| RATED BREAKING CAPACITY, AC-23A 690 V (A) | 5040 |
| ELECTRICAL ENDURANCE (NUMBER OF OPERATIONS) | 2000 |
| MECHANICAL ENDURANCE (NUMBER OF OPERATIONS) | 10000 |
| TERMINAL / BOLT SIZE CU (MM ²) | M12 |
| MAXIMUM TERMINAL TORQUE (NM) | 50..75 |
| SWITCH TYPE | Load Break Switch |