



## LoadSafe KVKE 363

|                |               |
|----------------|---------------|
| PRODUCT NUMBER | 21414         |
| GTIN           | 6419410214145 |
| E-NUMBER FI    | 3609679       |
| ETIM CLASS     | EC001040      |

### MEASUREMENTS

|            |           |
|------------|-----------|
| HEIGHT     | 163 mm    |
| WIDTH      | 132 mm    |
| DEPTH      | 118 mm    |
| VOLUME     | 2.5389 l  |
| NET WEIGHT | 1.3297 kg |

### DIMENSIONAL DRAWING

### LOGISTICAL DATA

|                |           |
|----------------|-----------|
| SALES UNIT     | 1         |
| PACKAGE SIZE 1 | 1         |
| PACKAGE SIZE 1 | 1.3297 kg |
| WEIGHT         |           |

## TECHNICAL DATA

|  |     |
|--|-----|
| NUMBER OF POLES  | 3   |
| RATED OPERATIONAL CURRENT<br>AC-23A 415 V, IE (A)                                      | 63  |
| RATED OPERATIONAL CURRENT<br>AC-23A 690 V, IE (A)                                      | 63  |
| RATED OPERATIONAL POWER, 3-<br>PHASE 1500 RPM SQUIRREL-CAGE<br>MOTOR AC-23A 690 V (KW) | 55  |
| RATED INSULATION VOLTAGE, UI<br>(V)  | 690 |
| NOMINAL VALUES WITH CABLE<br>SIZE (MM <sup>2</sup> )                                   | 16  |
| RATED THERMAL CURRENT, ITH<br>(A)  | 63  |
| RATED OPERATIONAL CURRENT<br>AC-21A 415 V, IE (A)                                      | 63  |
| RATED OPERATIONAL CURRENT<br>AC-21A 500 V, IE (A)                                      | 63  |
| RATED OPERATIONAL CURRENT<br>AC-21A 690 V, IE (A)                                      | 63  |
| RATED OPERATIONAL CURRENT<br>AC-22A 415 V, IE (A)                                      | 63  |
| RATED OPERATIONAL CURRENT<br>AC-22A 500 V, IE (A)                                      | 63  |
| RATED OPERATIONAL CURRENT<br>AC-22A 690 V, IE (A)                                      | 63  |
| RATED OPERATIONAL CURRENT<br>AC-23A 500 V, IE (A)                                      | 63  |
| RATED OPERATIONAL POWER, 3-<br>PHASE 1500 RPM SQUIRREL-CAGE<br>MOTOR AC-23A 415 V (KW) | 30  |
| RATED OPERATIONAL POWER, 3-<br>PHASE 1500 RPM SQUIRREL-CAGE<br>MOTOR AC-23A 500 V (KW) | 37  |

|  |             |
|--|-------------|
| RATED FUSED SHORT-CIRCUIT CURRENT, BACK-UP FUSE OPTION 1 (A) | 63          |
| RATED FUSED SHORT-CIRCUIT CURRENT, R.M.S. IQ OPTION 1 (KA)   | 50          |
| RATED IMPULSE WITHSTAND VOLTAGE, UIMP (KV)                   | 8           |
| RATED SHORT-CIRCUIT MAKING CAPACITY, ICM 690 V (KA)          | 6           |
| RATED SHORT-TIME WITHSTAND CURRENT 1 S, ICW 690 V (KA)       | 4           |
| RATED BREAKING CAPACITY, AC-23A 415 V (A)                    | 504         |
| RATED BREAKING CAPACITY, AC-23A 500 V (A)                    | 504         |
| RATED BREAKING CAPACITY, AC-23A 690 V (A)                    | 504         |
| ELECTRICAL ENDURANCE (NUMBER OF OPERATIONS)                  | 2000        |
| MECHANICAL ENDURANCE (NUMBER OF OPERATIONS)                  | 20000       |
| TERMINAL / BOLT SIZE CU (MM <sup>2</sup> )                   | 6..70       |
| MAXIMUM TERMINAL TORQUE (NM)                                 | 6           |
| FUSE TYPE: DIN   | 000/00      |
| SWITCH TYPE  | Switch Fuse |