

ConnectSafe
KL2X95N

PRODUCT NUMBER	37835
GTIN	6419410378359
E-NUMBER FI	1942071
ETIM CLASS	EC000897


MEASUREMENTS

HEIGHT	62.5 mm
WIDTH	42 mm
DEPTH	49 mm
VOLUME	0.1286 l
NET WEIGHT	0.1936 kg

LOGISTICAL DATA

PACKAGE SIZE 1	12
PACKAGE SIZE 1 WEIGHT	0.1936 kg

DIMENSIONAL DRAWING



We continuously improve our products; specifications, features and appearances may change without prior notice.

KATKO ConnectSafe

TECHNICAL DATA

NUMBER OF POLES	2
UL	UL 1059, CAN/CSA C22.2 No. 158-10
ATEX	No
TORQUE AL/CU (NM)	12 (6 - 50 mm^2) / 22 (70 - 95 mm^2)
KEY SIZE	Hex 6
IN (AL) (A)	400
IN (CU) (A)	490
AL MM^2	6-95
CU MM^2	6-95
NOMINAL VOLTAGE	1000V AC / 1500V DC
LINE/LOAD WIRE SIZE-STR CU/AL (KCMIL/AWG)	4/0 - 4
TORQUE AL/CU LB-IN	110 (1/0 - 4 AWG) / 200 (4/0 - 2/0 AWG)
AMPERE AL (A)	360
AMPERE CU (A)	460

We continuously improve our products; specifications, features and appearances may change without prior notice.